



Product Data Sheet Smart

May, 2023

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering
Class of use	ISO 10874 (EN 685)	
CE certification	EN 14041:2004/AC:2006	2701-0079-DoP-2021-11

TECHNICAL CHARACTERISTICS AND PERFORMANCES

	ISO 24346 (EN 428) Total tickness	2,20 mm		ISO 24341 (EN 426) Roll lenght Roll width	30m (15-30) 25m (15-25) 2,5; 3; 3,5m; 2m; 4m
	ISO 24340 (EN 429) Wear layer tickness	0,50 mm		ISO 717/2 Impact sound absorption	10 dB
	ISO 23997 (EN 430) Weight per m²	2,200 kg/m²		ISO 24343-1 (EN 433) Residual indentation	≤ 0,20 mm
	ISO 105 B02 Method 3 Light fastness	≥ 6		ISO 4918 (EN 425) Castor chair	excellent
	ISO 23999 (EN 434) Dimensional stability	Requirement by standard: < 0,4 % Tarkett result: ≤ 0,011 %		Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
	EN 1815 Static electrical propensity	≤ 2 kV (antistatic)		EN 13893 Slip resistance	
	EN 13501-1 Fire classification	Bfl-s1		EN 12524 Thermal resistance	0,02 - 0,03m²/kW

Wear layer binder content ISO 11638 Type I



CHIPS
CHIPS®
EFFECT



TITAN
PROTECTIVE
LAYER



2701-0079-DoP-2021-11

This product is
100% recyclable