

Petit Dune

10 mm

TOTAL HEIGHT

The Enhanced Revolution.

Petit Dune takes innovation to the next level by refining the revolutionary combination of tape and textured yarn in Turfgrass's short-pile artificial grass range. This unique formula not only ensures an exceptionally natural look but also offers incredible resilience and a highly realistic finish.

STANDARD ROLLS

Pile out 2x35 m - 4x35 m

WARRANTY (Years - KLy)

3 - 400 Kly*

TESTS AND CERTIFICATES

DURABILITY_

- ISO 9001_QUALITY MANAGEMENT
- Colour fastness ≥ 4
- Water permeability 60l/min/m²

ENVIRONMENT_

- ISO 14001_ENVIRONMENTAL MANAGEMENT

SAFETY_

- Fire certification: Efl
- ISO 45001_Occupational health and safety management systems
- Social Audit, 2-Pillar SMET

DAG.410.MAR.15 / 2 / 1-9-24

REMARKS

In case infill is added to the Turfgrass artificial grass, please use rounded (non-angular), sieved, washed and dried silica sand. The use of any other type of infill material will invalidate the Turfgrass warranty.

*The standard warranties are applicable for regions with Global horizontal irradiation lower than or equal to 1800 KWH/m²/year or 155 KLy/m²/year. For regions with Global Horizontal Irradiation more than 1800 KWH/m²/year or 155 KLy/m²/year, please refer to our warranty statement.

Technical characteristics




Yarn

Type:	Tape + Texturized
Composition:	100% PP
Dtex.:	4000 DTex (±5%)
Pile weight:	525 gr/m ² (±10%)
Colors:	Tape: Green Texturized: Cream / Green



Tufting

Gauge:	3/16"
Pile height:	9 mm (±5%)
Total height:	10 mm (±5%)
Stitches:	260 lm (±10%) - 54600 m ² (±10%)



Backing construction

Primary backing:	Single Backing 100% pp, uv Stabilized
Finishing:	PRECOAT MARINE BACKING



Final product

Total weight:	930 gr/m ² (±10%)
---------------	------------------------------



In order to constantly improve the quality of our products to the latest technical standards, Turfgrass® reserves the right to modify any of the technical characteristics. The stated values are approximate average values and may vary by ±10% (fibre height ±5%) due to technical reasons.

