

ESSENZ


CARPETS MADE TO LAST

DURABLE


SOLID

RESILIENT


FAIRFIELD DESIGN



▲ SMB: LFDC.0862 | 400 cm



▲ SMB: LFDC.0443 | 400 cm



▲ SMB: LFDC.0270 | 400 cm



▲ SMB: LFDC.0865 | 400 cm



ESSENZ

CARPETS MADE TO LAST

DURABLE

SOLID

RESILIENT



▲ SMB: LFDS.0805 | 400 cm



▲ SMB: LFDS.0862 | 400 cm



▲ SMB: LFDS.0865 | 400 cm



▲ SMB: LFDS.0882 | 400 cm



▲ SMB: LFDS.0113 | 400 cm



▲ SMB: LFDS.0270 | 400 cm



▲ SMB: LFDS.0450 | 400 cm



▲ SMB: LFDS.0443 | 400 cm




▲ SMB: LFDS.0591 | 400 cm



▲ SMB: LFDP.0450 | 400 cm



▲ SMB: LFDP.0805 | 400 cm



▲ SMB: LFDP.0270 | 400 cm



▲ SMB: LFDP.0882 | 400 cm



▲ SMB: LFDP.0443 | 400 cm



ESSENZ

CARPETS MADE TO LAST

DURABLE

SOLID

RESILIENT

FAIRFIELD DESIGN

Poolsamenstelling Nature du velours Pile composition Polmaterial Composizione felpa PP	Tuftdoek Premier dossier Primary backing Trägermaterial Tela di supporto woven	Rugtype Envers Secondary backing Rücken Sottofondo SMB	Totale dikte Hauteur totale Total height Gesamthöhe Spessore totale ± 10 mm
Nuttige poolhoogte Hauteur du velours utile Effective pile height Tatsächliche Florhöhe Spessore felpa utile ± 8,5 mm	Breedte Largeur Width Breite Altezza (FDC - FDP) ± 400 cm	Breedte Largeur Width Breite Altezza (FDS) ± 400 & 500 cm	Aantal noppen/m² Nombre de points/m² Number of knots/sqm Noppenzahl/m² Numero di punti/mq ± 159.570
Poolinzetgewicht/m² Poids mis en oeuvre/m² Pile weight/sqm Poleinsatzgewicht/m² Peso felpa/mq ± 2.290 gr	Totaal gewicht/m² Poids total/m² Total weight/sqm Poleinsatzgewicht/m² Peso totale/mq ± 1.450 gr	EN 13501-1 Brandgedrag Comportement au feu Fire behaviour Brennverhalten Reazione al fuoco E_{fl}	EN 1307-2004 Classificatie Classification Classification Klassifizierung Classificazione Cl. 22 Domestic General
ISO 140/8 Contactgeluidsisolatie Isolation aux bruits d'impact Impact sound insulation Trittschallverbesserungsmaß Miglioramento acustico ± 25	DIN 52612 Warmteoorlaatweerstand Résistivité thermique Thermal retention Wärmedurchlaßwiderstand Resistenza termica ± 0,1 m²/kW	TOG rating ± 1	ISO 105 B02 2000 Lichtechtheid Solidité à la lumière Lightfastness Lichtechtheid Solidità colori alla luce ≥ 5
ISO 105 E01 2002 Watrechtheid verkleuring Solidité à l'eau changement couleur Waterfastness change in colour Wasserechtheit Änderung der Farbe Solidità colori all'acqua cambio colore ≥ 3-4	ISO 105 E01 2002 Watrechtheid uitbloeding Solidité à l'eau dégorgeement Waterfastness staining Wasserechtheit anbluten Solidità colori all'acqua sfumatura colore ≥ 2-3	ISO 105 X12 2001 Wrijfechtheid droog Solidité au frottement sec Rubbingfastness dry Reibungechtheit trocken Solidità colori allo sfregamento a secco ≥ 3-4	ISO 105 X12 2001 Wrijfechtheid nat Solidité au frottement humide Rubbingfastness wet Reibungechtheit nass Solidità colori allo sfregamento umido ≥ 3

(±) These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to improve technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. The natural characteristics of woollen products result in shade variations & slight blemishes. They cannot be avoided without destroying the very nature of the product itself. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet. For other languages see: www.lano.com

