

TECHNICAL DATA

CERTIFICATION AND CLASSIFICATION	STANDARD	ModularT 70	
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings	
CE certification	EN 14041		YES
Classification	EN ISO 10874	  	Residential: 23 Commercial: 34 Industrial: 43

TECHNICAL CHARACTERISTICS	STANDARD	ModularT 70	
Total thickness	EN ISO 24346		2,5 mm
Wear layer thickness	EN ISO 24340		0,7 mm
Bevelled edges			YES
Total weight	EN ISO 23997		3200 g/m²
Binder content	EN ISO 10582		Type I
Form of delivery	ISO 24342 (EN 427)	Plank 20x120 cm, 18 planks/box=4,32m², 60 boxes/pallet Tile 66,5x66,5 cm, 10 tiles/box=4,42m², 60 boxes/pallet Tile 50x100 cm, 8 tiles/box=4m², 70 boxes/pallet	

TECHNICAL PERFORMANCES	STANDARD	ModularT 70	
Dimensional stability	EN ISO 23999		Average measured value ≤ 0,10 %
Reaction to fire	EN 13501-1		Bfls1 on concrete substrate
Residual indentation	EN ISO 24343-1		≤ 0,10 mm
Furniture leg	EN ISO 16581		No damage
Castor chair	EN ISO 4918		No damage
Curl resultant to heat	EN ISO 23999		≤ 2 mm
Thermal resistance	EN ISO 10456		0,02 - 0,03 m² K/W
Impact sound reduction - ΔLw	EN ISO 717-2		ΔLw = 8 dB
Reduction of in-room impact noise	NF S 31- 074		L n,e,w = 73 dB
Light fastness	EN ISO 105-B02		≥ 6
Slip resistance	EN 13893 DIN EN 16165 Annex B		μ ≥ 0.3 → Class DS R9/R10 depending on embossing type
Static Electrical Propensity	EN 1815		≤ 2 kV
Underfloor heating			Suitable (subfloor temperature maximum 27°C)

